



ODIE'S OIL

ODYSSEUS CORNWALL'S OUTSTANDING OILS AND WAXES



The Back Story

The Odie's (Odysseus Cornwall's Outstanding Oils and Waxes) is a family manufacture in Florida, USA since 1982.

The founder is a woodworking specialist who has a wide-plank flooring company. He was unhappy with both the look of mainstream conventional wood finishes and the risk of exposure to the chemicals and toxins offered by the finish and chemical products industry, so the developer of Odie's Oil searched for safer alternatives to mainstream industry offerings.

“Can a finish be non-toxic and still produce an effective result?”

This was the question to which **Odie's Oil** became the answer.

It quickly gathered a fan base that referred to it as the “magic finish”. Odie's works harmoniously with the natural oils and waxes in the wood.

No solvents, no toxins, easy to use and an incredibly lustrous sheen! Odie's is the holy grail of finishes!



Odie's is food-safe, pet-safe, and people-safe from “cradle to grave”.

Odie's Oil

info@odiesoil.eu

www.odiesoil.eu

**ODIE'S
OIL**

European Headquarters

H-1077 Budapest, Wesselényi u. 16.

+36 1 264 0444

Take your work to the next level and get to know the unique trend of surface treatment!

Committing to Odie's is about standing up for your family, co-workers, and the Earth – not exposing any of them to contact with hazardous substances.

We would love to welcome you to the growing worldwide family of Odie's Oil dealers and distributors – or users.



Join our revolution and give it a try!
We look forward to your reaction.

Odie's Oil

info@odiesoil.eu

www.odiesoil.eu

**ODIE'S
OIL**

European Headquarters

H-1077 Budapest, Wesselényi u. 16.

+36 1 264 0444



THE BENEFITS OF ODIE'S OILS

Does not contain evaporating chemicals
no unpleasant scent

100% organic ingredients
it's okay if the kids taste it

Does not dry out
no problem if the workflow is interrupted

Simple coloring
achieve your unique desired color by adding
Mr. Cornwall's Creative Colours

Easy to apply
does not stick or flow, unlike other oils

Easy maintenance
easy to repair locally, no repeated
sanding necessary

Dust does not stick to the surface
easy to clean

No water on the surface
water repellent effect

Economical packaging
one bottle is sufficient to treat a
surface of about 25-40 nm

Best quality product on the market!

Odie's Oil

info@odiesoil.eu

www.odiesoil.eu

**ODIE'S
OIL**

European Headquarters

H-1077 Budapest, Wesselényi u. 16.

+36 1 264 0444

Odie's Instruction Manual

Thank you so much for choosing Odie's! The Odie's Finishes are true hard wax oils and are proudly made of 100% natural ingredients. Unlike other finishes, it takes just a few easy steps to ensure a brilliant and long-lasting finish for your project. We want you to succeed!

- Stir or mix your jar (Oil Only) well as ingredients may settle over time.
- Tools needed: A **non-woven pad** (rated above the grit or micron the piece has been sanded to) / A **Clean** Cotton Terry Cloth Towel.
- Use the **non-woven pad** to work the product into your project surface. The friction from the application helps drive the product to the surface. Remember: **A little Odie's goes a long way, so don't overdo it!**
- After working the product into the surface with the pad, allow it to set for 10 minutes to 3 hours (depending on the product used and surface applied to). You can wait, but your buff/wipe off may be a bit tougher. **Do not allow the product to set for more than 12 hours! This will require a re-application to re-activate the finish for a proper buff/wipe off.**
- After waiting for the product to set up, take a clean terry (100% cotton) cloth towel and proceed to **BUFF/WIPE OFF ALL** the product from your project surface. When your towel has loaded up with product, switch to a new clean terry cloth towel until the entire surface is buffed off clean and NO product REMAINS. If you can swipe a clean finger across the surface and make no mark you are done.
- Cure time for Odie's Universal and Super Duper light oil: most surfaces can be used within 24 hours and can be exposed to liquids within 3 to 5 days.
- Cure time for the rest of our finishes: your piece can be handled almost immediately after buffing however, we suggest you give it a day or two to further the cure before any use. If you know the piece is going to be exposed to water or liquids, we suggest you give it 5 days of cure time for best results. On exterior decks, 4-5 days of dry weather is all that is required.
- Additional coats of Odie's products can be applied using these same easy steps above. We suggest waiting 24 hours in between coats.

- For **Epoxy/Resin** projects we recommend using less oil than on wood - follow the same application process.
- For **Super Duper Oil** and **Super Duper Dark Oil** wipe, brush, roll or spray on and work into the surface when possible. Be sure to wipe away any excess oil that remains on the surface. Formulated for **wood, stone & concrete, clay & brick, metal, plastic.**
- For **concrete, leather, or metal application**- don't let the oil sit, BUFF OFF immediately.
- When applying to **concrete**, the initial cure is much quicker - in most cases, the surface can be used within 8 hours.
- For repairs or a maintenance re-coat, 10 hours of cure time is sufficient before use.
- **We don't recommend our Dark finishes for exterior use, all the rest of Odie's products are excellent for both interior and exterior use.**

If you have any questions on the process or finishing tools please visit our website at <https://odiesoil.eu/faq/> for more information!

BUFF OFF



Get in touch with us!

Business Development: Tamás Kicska

tamas.kicska@timbart.hu

Technical Director: Márk Cselovszki

mark.cselovszki@timbart.hu



Odie's Oil European Head Office is located in Budapest, Hungary.

www.odiesoil.eu

Odie's Europe

info@odiesoil.eu

www.odiesoil.eu

**ODIE'S
OIL**

European Headquarters

H-1077 Budapest, Wesselényi u. 16.

+36 1 264 0444



Odie's Europe

info@odiesoil.eu

www.odiesoil.eu

**ODIE'S
OIL**

European Headquarters

H-1077 Budapest, Wesselényi u. 16.

+36 1 264 0444